

## AMENDMENT

## **Amendment to the Claims**

**In the Claims:**

Please cancel Claims 1-4, 6-8, and 13-15.

Please cancel previously non-elected Claims 21-55.

Please amend Claims 5, 9, 10, and 11 as follows:

1. (Cancelled)
2. (Cancelled)
3. (Cancelled)
4. (Cancelled)

5. (Twice Amended) [The] A contactless energy transfer apparatus [of Claim 1.] comprising:

**(a)** a portable receiving unit including:

(i) a receiver coil; and

(ii) a housing in which the receiver coil is disposed, said housing

**(b)** a flux generator including:

(i) a housing adapted to be disposed proximate to the housing of the receiving unit;

(ii) a magnetic field generator comprising at least one permanent magnet disposed within the housing of the flux generator; and

(iii) a prime mover drivingly coupled with the at least one permanent magnet, causing said at least one permanent magnet to move relative to the receiver coil, movement of said at least one permanent magnet producing a varying magnetic field that is coupled to the receiver coil, inducing an electrical current to flow in the receiver coil, wherein the prime mover is disposed outside the housing of the flux generator and is drivingly coupled [to said element of the magnetic field generator] with said at least one permanent magnet through a driven shaft.

6. (Cancelled)  
7. (Cancelled)

9. (Amended) [The] A contactless energy transfer apparatus [of Claim 8] comprising:



1 shunt [that is moved by the prime mover], to cause the magnetic flux shunt to move between the  
2 shunt position and the unshunt position, thereby periodically shunting a magnetic field produced by  
3 said at least one permanent magnet of the magnetic field generator, causing the magnetic field to vary  
4 along a path that includes the receiver coil.

5 11. (Amended) [The] A contactless energy transfer apparatus [of Claim 1, further]  
6 comprising:

- 7 (a) a portable receiving unit including:
  - 8 (i) a receiver coil; and
  - 9 (ii) a housing in which the receiver coil is disposed, said housing  
10 supporting the receiver coil; and
- 11 (b) a flux generator including:
  - 12 (i) a housing adapted to be disposed proximate to the housing of the  
13 receiving unit;
  - 14 (ii) a magnetic field generator comprising at least one permanent magnet  
15 disposed within the housing of the flux generator;
  - 16 (iii) a prime mover drivingly coupled with the at least one permanent  
17 magnet, causing said at least one permanent magnet to move relative to the receiver coil, movement  
18 of said at least one permanent magnet producing a varying magnetic field that is coupled to a core of  
19 the receiver coil, inducing an electrical current to flow in the receiver coil; and
  - 20 (iv) an adjustment member that is selectively actuatable to change a  
21 maximum magnetic flux that is coupled to the core of the receiver coil.

22 12. (Original) The energy transfer apparatus of Claim 11, wherein the adjustment member  
23 controls a speed with which the element of the magnetic field generator is moved.

24 13. (Cancelled)

25 14. (Cancelled)

26 15. (Cancelled)

27 16 - 20. (Previously cancelled)

28 21-55. (Cancelled - Previously Withdrawn (non-elected claims))

29 ///

30 ///